

Lanier Worldwide, Inc. 2300 Parklake Drive, NE Atlanta, GA USA 30345-2979

# MATERIAL SAFETY DATA SHEET

**Emergency Telephone:** 800-551-3087

# **Section 1: Chemical Product and Company Information**

 Identity:
 Toner for 6517/6717/6616/6720
 MSDS No.
 CP- 261

 Product ID:
 117-0154
 Issued: 02/08/2005
 02/08/2005

 Supersedes:
 06/10/1998

& Common Names: Black Toner for 6517, 6717, 6616, Approved by: Black Toner for 6517, 6717, 6616, Approved by: EH&S Department 770-496-9500 Larry Choskey, Manager, CEH&S

Uses: Lanier 6517, 6717, 6616, 6720 European Walter Fricke, Manager, Safety &

Contact: Environment,

Chemical Mixture Lanier Worldwide, Inc.
Formula: Im Taubental D-41468 Neuss,
Germany +49-2131-387-177

Section 2: Composition / Information on Ingredients Component Percent CAS No. **Exposure Limits** Source Styrene-acrylic resin 85 - 9025153-46-2 Not listed N/a 3.5 mg/m<sup>3</sup> 3.5 mg/m<sup>3</sup> Carbon black 1333-86-4 OSHA PEL 5 - 10**ACGIH TWA** Not listed 1 - 69003-07-0 N/a 10 mg/m<sub>3</sub> 10 mg/m<sub>3</sub> Organic pigment **OSHA PEL** 116810-46-9 1 - 6**ACGIH TWA** OSHA PEL Silica < 1 7631-86-9 6 mg/m<sup>3</sup> 10 mg/m<sup>3</sup> **ACGIH TWA** 

\*PEL as the product: 15mg/m³ (total dust), 5mg/m³ (respirable dust) \*TLV as the product: 10mg/m³ (total dust), 5mg/m³ (respirable dust)

## **Section 3: Hazards Identification**

HMIS Rating:
FLAMMABILITY = 1 HEALTH = 1
REACTIVITY = 0 SPECIAL = none

Health Hazards (Acute, Chronic, Immediate and Potential): Minimum irritation to respiratory tract may occur as with exposure to any non-toxic dust. May cause gasping if inhaled. Inhalation should be avoided. May cause temporary eye discomfort. Health Hazards of Long Term exposure (Chronic): Prolonged inhalation of excessive dust may cause lung damage. It is attributed to "lung overloading", a generic response to excessive amounts of any dust retained in the lungs for a prolonged interval. Use of this product, as intended, does not result in inhalation of excessive dust.

**Carcinogenicity:** Carbon Black was reclassified as a Group 2B by the IARC in 1996 based upon the result of only the inhalation study in rats. However, there was not observed the incidence of tumors on the test results on dermal or oral studies. Also, 2-years inhalation study using a typical toner containing carbon black showed no association between toner exposure and animal tumors.

#### **Section 4: First Aid Measures**

Gargle with water. Remove to fresh air if effects occur. Get medical attention if needed.

Skin Contact:

Wash with soap and water.

Gargle with water. Remove to fresh air if effects occur. Get medical attention if needed.

Eye Contact: with water for 15 minutes. Get medical attention if needed.

Dilute stomach contents with several

glasses of water. Get medical attention.

#### Section 5: Fire Fighting Measures

Suitable extinguishing media: CO<sub>2</sub>, dry chemical, foam or water. Extinguishing media which may not be used for safety

reasons: none

Special protective equipment for fire fighters: none

UEL: n/a LEL: n/a

#### **Section 6: Accidental Release Measures**

Spill / leak Procedures: If spilled, sweep up using an approved toner vacuum with a 0.5 micron filter or smaller, such as the Atrix AAA Toner Vacuum or 3M Toner Vacuum. Use of a vacuum cleaner not rated for toner particles, could result in a fire or personal injury. Remove residue with soap and cold water.

Miscellaneous: Keep product out of sewers and watercourses.

Personal protection: Avoid inhalation of dust.

### Section 7: Handling and Storage

Special Handling: Cleanse skin after contact before breaks or meals, and end of workday.

Do not handle in areas where the wind blows.

Minimize the breathing of dust.

Special Storage: Avoid direct sunlight. Keep out of reach of children. Store in a cool, dry place. Below 35C (95F)

## **Section 8: Exposure Control and Personal Protection Information:**

Respiratory Protection: none required under normal use. Hand Protection: none required under normal use.

Eye Protection: none required under normal use. Skin Protection: none required under normal use.

#### **Section 9: Physical and Chemical Properties**

CHARACTERISTICS:

Appearance: Black Melting point: 130° - 170° C

Powder Vapor pressure: Form: N/a Practically odorless Vapor density: Odor: N/a Solubility in Water: Negligible Evaporation rate: N/a Specific gravity: 0.2 - 0.5Boiling point: N/a

#### Section 10: Stability and Reactivity

Conditions to avoid: none Materials to avoid: none Stability: Stable

Hazardous decomposition products: Will not occur

#### Section 11: Toxicological Information:

Ames test negative

Acute oral toxicity: n/a

Special effects: Carcinogenicity: In 1996 the IARC reclassified Carbon Black as a Group 2B carcinogen (possible human carcinogen). This evaluation is given to carbon black for which there is inadequate human evidence, but sufficient animal evidence. The latter is based upon the development of lung tumors in rats receiving chronic inhalation exposures to free carbon black at levels that induce particle overload of the lung. Studies performed in animal models other than rats have not demonstrated an association between carbon black and lung tumors. Moreover, 2-years cancer bioassay using a typical toner preparation containing carbon black did not demonstrate an association between toner exposure and tumor development in rats.

#### Section 12: Environmental / Ecological Information

Environmental Degradation: Not known Bioaccumulation: Not known in bioaccumulation

# **Section 13: Disposal Consideration**

Used Toner should be disposed of under conditions that meet all federal, state and local environmental regulations. Disposal regulations vary from locality to locality; therefore consult your local Lanier office or the EPA to determine the proper method for disposal. Do not incinerate loose or spilled Toner.

## Section 14: Transportation Information

International regulations:

RID/ADR Not applicable ICAO-TI/ATA-DGR Not applicable UN Classification Number Not applicable IMDG Code Not applicable

Specific precautionary transport measures: Avoid direct sunlight. Do not keep over 35°C (95°F).

Specific material to avoid: None in normal use.

## **Section 15: Regulatory Information**

Regulation: not available

#### **Section 16: Miscellaneous Information**

Judgment as to the suitability of information contained herein for user's purposes is the responsibility of the purchaser. Therefore, although reasonable care has been taken in the preparation of this information, Lanier Worldwide, Inc. extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information for application to user's intended purposes or for consequences of its use. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we do not guarantee that these are the only hazards that exist.

Information on this data sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. On the basis of the data available to us, this product is not a dangerous substance. One should, however, observe the usual precautionary measures for dealing with chemicals.